

屋内照明器具特性	
品番 (品名)	L G B 8 1 7 7 4
光源	LED3500_70_4530 ×1 4530.0 lm
管理番号	K0161533 (0) DR 1
B Z 分類	B Z 8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		50 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		50 %																							
保守率		良 中 否	0.63	0.6	45	33	25	19	41	30	23	18	34	25	19	15	27	20	16	12	7				
			0.6	0.8	53	41	33	27	49	38	31	25	40	32	26	21	32	26	21	17	11				
				1.0	59	48	39	33	54	44	36	31	45	37	31	26	36	30	25	21	13				
			0.56	1.25	65	54	46	40	59	50	42	37	49	42	36	31	40	34	29	26	17				
下方投影面積		cm ²		1.5	69	59	51	45	63	54	47	41	52	45	40	35	42	37	33	29	19				
				2.0	75	66	59	53	68	61	54	49	57	51	46	42	46	42	38	34	23				
等価発光面積		cm ²		2.5	78	70	64	58	72	65	59	54	60	55	50	46	49	45	41	38	26				
				3.0	81	74	68	63	74	68	63	58	62	58	53	50	51	48	44	41	28				
1.5m		2.44 m	2.16 m	4.0	84	78	73	69	78	73	68	64	66	62	58	55	54	51	48	46	32				
2		3.22	2.71	5.0	86	82	77	73	80	76	72	68	68	64	61	58	56	53	51	49	34				
2.5		4	3.29	7.0	89	85	82	78	83	79	76	73	70	67	65	62	58	56	54	52	37				
3		4.79	3.88	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	56	40				

