

# 屋内照明器具特性

品番 (品名)	NNN62010K	
光源	LDA7L-H/S/6 ×1	810.0 lm
管理番号	K0178079(0)DB1	
BZ分類	BZ5/0.7/BZ4	

器具効率	44%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		44%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	2.5	2.0	1.6	1.4	2.4	1.9	1.6	1.4	2.3	1.9	1.6	1.4	2.2	1.9	1.6	1.4	1.3	
	中	0.6	0.8	2.9	2.4	2.1	1.9	2.9	2.4	2.1	1.9	2.8	2.4	2.1	1.9	2.7	2.3	2.0	1.8	1.8	
	否	0.56	1.0	3.2	2.8	2.4	2.2	3.2	2.7	2.4	2.2	3.0	2.7	2.4	2.2	2.9	2.6	2.4	2.2	2.1	
			1.25	3.5	3.1	2.8	2.5	3.4	3.0	2.8	2.5	3.3	3.0	2.7	2.5	3.2	2.9	2.7	2.5	2.4	
下方投影面積	cm <sup>2</sup>		1.5	3.7	3.3	3.0	2.8	3.6	3.3	3.0	2.8	3.5	3.2	2.9	2.7	3.3	3.1	2.9	2.7	2.6	
等価発光面積	cm <sup>2</sup>		2.0	3.9	3.6	3.4	3.1	3.8	3.6	3.3	3.1	3.7	3.5	3.3	3.1	3.6	3.4	3.2	3.1	3.0	
取付高さ	器具間隔最大限		2.5	4.1	3.8	3.6	3.4	4.0	3.8	3.5	3.4	3.9	3.7	3.5	3.3	3.7	3.6	3.4	3.3	3.2	
	横方向 (A)	縦方向 (B)	3.0	4.2	3.9	3.7	3.6	4.1	3.9	3.7	3.5	4.0	3.8	3.6	3.5	3.9	3.7	3.6	3.5	3.3	
Hm	1.25Hm	1.25Hm	4.0	4.3	4.1	4.0	3.8	4.2	4.1	3.9	3.8	4.1	4.0	3.8	3.7	4.0	3.9	3.8	3.7	3.6	
			5.0	4.4	4.2	4.1	4.0	4.3	4.2	4.1	3.9	4.2	4.1	4.0	3.9	4.1	4.0	3.9	3.8	3.7	
			7.0	4.5	4.4	4.3	4.2	4.4	4.3	4.2	4.1	4.3	4.2	4.1	4.1	4.2	4.1	4.0	4.0	3.9	
			10.0	4.5	4.5	4.4	4.3	4.5	4.4	4.3	4.3	4.4	4.3	4.3	4.2	4.3	4.2	4.2	4.1	4.0	

