

屋内照明器具特性	
品番 (品名)	L G B 1 0 4 2 6
光源	LED2700_70_234 ×1 234.0 l m
管理番号	K0150711 (0) DB 1
B Z 分類	BZ3 / 1.8 / BZ4

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束 下方光束		3 % 97 %	室指数	照明率 (X0.01) ZCM																					
保守率		良 中 否	0.67	0.6	63	53	46	41	62	52	45	41	59	51	45	41	57	50	44	40	38				
			0.63	0.8	72	62	55	50	70	61	55	50	68	60	54	50	65	58	53	49	47				
			1.0	78	68	62	57	76	68	61	56	73	66	60	56	70	64	59	55	53					
			0.56	1.25	83	75	68	63	81	73	68	63	78	71	66	62	75	70	65	61	59				
下方投影面積 等価発光面積		cm ² cm ²	1.5	86	79	73	68	85	78	72	68	82	76	71	67	79	74	69	66	63					
			2.0	91	85	80	75	90	84	79	75	86	81	77	74	83	79	75	72	70					
取付 高さ	器具間隔最大限		2.5	94	89	84	80	93	88	83	79	89	85	81	78	86	83	80	77	74					
	横方向 (A) 縦方向 (B)		3.0	96	92	87	84	95	90	86	83	91	88	84	82	88	85	83	80	77					
H m	0.96 H m 0.96 H m		4.0	99	95	92	89	97	94	91	88	94	91	89	86	91	89	86	84	81					
			5.0	101	97	95	92	99	96	93	91	96	93	91	89	93	91	89	87	84					
			7.0	103	100	98	96	101	99	97	95	98	96	94	93	95	93	92	91	87					
			10.0	104	102	101	99	102	101	99	98	99	98	97	95	96	95	94	93	90					

