

屋内照明器具特性	
品番 (品名)	NND26011K
光源	LEDBLUE_90_7.6 x1 7.6 l m
管理番号	K0146262(0)DD1
BZ分類	BZ3/2.8/BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.88 中 0.86 否 0.81	0.6	62	52	45	40	61	51	45	40	59	50	44	40	56	49	43	39	38	
		0.8	72	62	55	50	70	61	55	50	68	60	54	50	65	58	53	49	47	
		1.0	78	69	62	58	76	68	62	57	73	66	61	57	71	64	60	56	54	
		1.25	83	75	69	64	82	74	68	64	78	72	67	63	76	70	66	62	60	
下方投影面積	c m <sup>2</sup>	1.5	87	79	74	69	85	78	73	69	82	76	71	68	79	74	70	67	64	
		2.0	91	85	80	76	90	84	79	76	86	82	78	74	83	79	76	73	70	
取付高さ	器具間隔最大限		2.5	94	89	85	81	93	88	84	80	89	85	82	79	86	83	80	77	74
	横方向 (A)	縦方向 (B)	3.0	96	92	88	84	95	90	87	84	91	88	85	82	88	85	83	80	77
H m	0.86 H m	1.28 H m	4.0	99	95	92	89	97	94	91	88	94	91	89	86	91	89	86	84	81
			5.0	100	97	95	92	99	96	93	91	96	93	91	89	93	91	89	87	84
			7.0	102	100	98	96	101	98	96	95	97	96	94	92	94	93	92	90	87
			10.0	104	102	100	99	102	100	99	98	99	98	96	95	96	95	94	93	89

