

屋内照明器具特性	
品番 (品名)	L G W C 8 0 4 0 7
光源	LED2700_70_377 x1 377.0 lm
管理番号	K0160262 (0) DR 1
B Z 分類	B Z 1 0

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				ZCM
保守率		良 中 否	0.63	0.6	0.56	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	3		
			0.6	0.8	51	38	29	23	46	35	27	21	37	28	22	17	29	22	17	13	6				
			0.56	1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9				
			1.25	62	50	41	35	56	46	38	32	46	38	31	26	36	30	25	21	11					
下方投影面積		cm ²	1.5	66	55	47	40	60	51	43	37	49	42	35	30	39	33	28	24	14					
等価発光面積			cm ²	2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18				
				2.5	76	67	60	54	69	62	55	50	57	51	46	42	46	41	37	34	21				
取付高さ	器具間隔最大限			3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	37	24				
	Hm0.00Hm0.00Hm		4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	45	42	27					
			5.0	85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30					
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34					
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	58	57	55	53	37					

