

屋内照明器具特性

品番 (品名)	YYY46025Z	
光源	LED3000_70_2550 x1	2550.0lm
管理番号	K0148447(0)DB1	
BZ分類	BZ4/0.7/BZ5/0.9/BZ6/1.1/BZ7/1.4/BZ8/1.8/BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		100%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	0%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0
	中	0.67	0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	11	0
	否	0.63	1.0	56	47	40	35	48	40	35	31	33	28	24	22	19	16	14	13	0
下方投影面積		cm ²	1.25	61	53	47	42	52	46	40	36	36	31	28	25	20	18	16	15	0
	等価発光面積	cm ²	1.5	65	57	51	46	56	49	44	40	38	34	31	28	22	20	18	17	0
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	64	61	57	54	44	42	40	38	26	24	23	22	0
Hm	0.00Hm	0.00Hm	4.0	78	74	71	67	67	64	61	59	46	44	43	41	27	26	25	24	0
			5.0	79	76	73	71	68	66	64	61	47	46	44	43	27	27	26	25	0
			7.0	81	79	77	75	70	68	66	65	49	48	46	45	28	28	27	27	0
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	29	28	28	0

