

屋内照明器具特性	
品番 (品名)	L G W8 0 4 3 3
光源	LED5000_70_410 ×1 410.0 lm
管理番号	K0160291 (0) DR 1
B Z 分類	B Z 1 0

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		5 0 %																				
保守率		良	0 . 6 3	0 . 6	4 3	3 0	2 2	1 6	3 9	2 7	2 0	1 4	3 1	2 2	1 6	1 2	2 5	1 7	1 2	9	3	
		中	0 . 6	0 . 8	5 1	3 8	2 9	2 3	4 6	3 5	2 7	2 1	3 7	2 8	2 2	1 7	2 9	2 2	1 7	1 3	6	
		否	0 . 5 6	1 . 0	5 7	4 4	3 5	2 8	5 1	4 0	3 2	2 6	4 2	3 3	2 6	2 1	3 3	2 6	2 1	1 7	9	
		1 . 2 5	6 2	5 0	4 1	3 5	5 6	4 6	3 8	3 2	4 6	3 8	3 1	2 6	3 6	3 0	2 5	2 1	1 1			
下方投影面積		c m ²	1 . 5	6 6	5 5	4 7	4 0	6 0	5 1	4 3	3 7	4 9	4 2	3 5	3 0	3 9	3 3	2 8	2 4	1 4		
			等価発光面積	c m ²	2 . 0	7 2	6 2	5 4	4 8	6 6	5 7	5 0	4 4	5 4	4 7	4 2	3 7	4 3	3 8	3 3	3 0	1 8
取付高さ	器具間隔最大限		2 . 5	7 6	6 7	6 0	5 4	6 9	6 2	5 5	5 0	5 7	5 1	4 6	4 2	4 6	4 1	3 7	3 4	2 1		
	横方向 (A) 縦方向 (B)		3 . 0	7 9	7 1	6 4	5 8	7 2	6 5	5 9	5 4	6 0	5 4	5 0	4 5	4 8	4 4	4 0	3 7	2 4		
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	8 2	7 6	7 0	6 5	7 6	7 0	6 5	6 0	6 3	5 9	5 4	5 1	5 1	4 8	4 5	4 2	2 7		
			5 . 0	8 5	7 9	7 4	6 9	7 8	7 3	6 8	6 4	6 5	6 1	5 8	5 4	5 3	5 0	4 8	4 5	3 0		
			7 . 0	8 8	8 3	7 9	7 5	8 1	7 7	7 3	7 0	6 8	6 5	6 2	5 9	5 6	5 4	5 1	4 9	3 4		
			1 0 . 0	9 0	8 7	8 3	8 0	8 3	8 0	7 7	7 5	7 1	6 8	6 6	6 4	5 9	5 7	5 5	5 3	3 7		

