

屋内照明器具特性

品番 (品名)	L G W 4 5 9 4 0	
光源	LED2700_70_110 x1	110.0 l m
管理番号	K0151814 (0) DB 1	
B Z 分類	BZ10 / 1.4 / BZ9	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 81 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	19 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.69	0.6	43	31	24	19	37	28	21	17	27	20	16	12	18	13	10	8	1
	中	0.67	0.8	51	40	32	27	44	35	28	24	32	26	21	17	22	17	14	11	2
	否	0.63	1.0	57	46	39	33	49	41	34	29	36	30	25	22	24	20	17	14	3
下方投影面積	等価発光面積	c m ²	1.25	62	52	45	39	54	46	40	35	40	34	30	26	27	23	20	18	5
			1.5	66	57	50	44	58	50	44	39	43	37	33	30	29	25	23	20	6
取付高さ	器具間隔最大限		2.0	71	63	57	52	63	56	51	46	46	42	38	35	32	29	26	24	7
	横方向 (A)	縦方向 (B)	2.5	74	68	62	57	66	60	55	51	49	45	42	39	33	31	29	27	9
H m	0.00H m	0.00H m	3.0	77	71	66	61	68	63	59	55	51	47	44	42	35	33	31	29	10
			4.0	80	75	71	67	71	67	63	60	53	50	48	45	37	35	33	31	11
			5.0	82	78	74	71	72	69	66	63	55	52	50	48	38	36	35	33	12
			7.0	84	81	78	75	75	72	70	67	57	55	53	51	39	38	37	36	13
			10.0	86	84	81	79	76	74	72	71	58	57	55	54	41	40	39	38	14

