

屋内照明器具特性	
品番 (品名)	NNY20020
光源	LED5000_85_27500 ×1 27500.0 lm
管理番号	K0147640(1)DB1
BZ分類	BZ1/3.5/BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	7%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	74	66	61	58	73	66	61	58	71	64	60	57	69	63	59	57	55
	中	0.81	0.8	82	74	69	66	80	74	69	65	77	72	68	65	75	70	67	64	62
	否	0.77	1.0	86	80	75	71	85	79	74	71	82	77	73	70	79	75	72	69	67
			1.25	90	84	80	76	88	83	79	76	85	81	77	75	82	79	76	73	71
下方投影面積	c m <sup>2</sup>		1.5	93	87	83	80	91	86	82	79	88	84	80	78	85	81	79	76	74
	等価発光面積		c m <sup>2</sup>	2.0	96	92	88	85	94	90	87	84	91	88	85	82	88	85	83	81
取付高さ	器具間隔最大限		2.5	98	94	91	88	96	93	90	87	93	90	88	85	89	87	85	83	80
	横方向 (A)	縦方向 (B)	3.0	100	96	93	91	98	95	92	90	94	92	90	88	91	89	87	85	82
H m	0.93 H m	0.93 H m	4.0	101	99	96	94	99	97	95	93	96	94	92	91	92	91	89	88	84
			5.0	102	100	98	96	100	99	97	95	97	95	94	92	93	92	91	90	86
			7.0	104	102	101	99	102	100	99	98	98	97	96	95	95	94	93	92	88
			10.0	105	103	102	101	103	102	101	100	99	98	97	96	95	95	94	93	89

