

| 屋内照明器具特性 | |
|----------|--------------------------------|
| 品番 (品名) | NNY20005 |
| 光源 | LED5000_85_13800 ×1 13800.0 lm |
| 管理番号 | K0147640(1)DB1 |
| BZ分類 | BZ1/3.5/BZ2 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 7% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 93% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.83 | 0.6 | 74 | 66 | 61 | 58 | 73 | 66 | 61 | 58 | 71 | 64 | 60 | 57 | 69 | 63 | 59 | 57 | 55 |
| | 中 | 0.81 | 0.8 | 82 | 74 | 69 | 66 | 80 | 74 | 69 | 65 | 77 | 72 | 68 | 65 | 75 | 70 | 67 | 64 | 62 |
| | 否 | 0.77 | 1.0 | 86 | 80 | 75 | 71 | 85 | 79 | 74 | 71 | 82 | 77 | 73 | 70 | 79 | 75 | 72 | 69 | 67 |
| | | | 1.25 | 90 | 84 | 80 | 76 | 88 | 83 | 79 | 76 | 85 | 81 | 77 | 75 | 82 | 79 | 76 | 73 | 71 |
| 下方投影面積 | c m ² | | 1.5 | 93 | 87 | 83 | 80 | 91 | 86 | 82 | 79 | 88 | 84 | 80 | 78 | 85 | 81 | 79 | 76 | 74 |
| | 等価発光面積 | | c m ² | 2.0 | 96 | 92 | 88 | 85 | 94 | 90 | 87 | 84 | 91 | 88 | 85 | 82 | 88 | 85 | 83 | 81 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 98 | 94 | 91 | 88 | 96 | 93 | 90 | 87 | 93 | 90 | 88 | 85 | 89 | 87 | 85 | 83 | 80 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 100 | 96 | 93 | 91 | 98 | 95 | 92 | 90 | 94 | 92 | 90 | 88 | 91 | 89 | 87 | 85 | 82 |
| H m | 0.93 H m | 0.93 H m | 4.0 | 101 | 99 | 96 | 94 | 99 | 97 | 95 | 93 | 96 | 94 | 92 | 91 | 92 | 91 | 89 | 88 | 84 |
| | | | 5.0 | 102 | 100 | 98 | 96 | 100 | 99 | 97 | 95 | 97 | 95 | 94 | 92 | 93 | 92 | 91 | 90 | 86 |
| | | | 7.0 | 104 | 102 | 101 | 99 | 102 | 100 | 99 | 98 | 98 | 97 | 96 | 95 | 95 | 94 | 93 | 92 | 88 |
| | | | 10.0 | 105 | 103 | 102 | 101 | 103 | 102 | 101 | 100 | 99 | 98 | 97 | 96 | 95 | 95 | 94 | 93 | 89 |

