

屋内照明器具特性

品番 (品名)	NNY20006	
光源	LED5000_85_13800 ×1	13800.0 1 m
管理番号	K0147641 (5) DB 1	
BZ分類	BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	2 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	98 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	62	51	44	39	61	51	44	39	58	49	43	39	56	48	43	39	37
	中	0.81	0.8	73	63	56	51	71	62	56	51	69	61	55	51	66	60	54	51	49
	否	0.77	1.0	80	71	65	60	78	70	64	60	75	68	63	59	73	67	62	58	56
			1.25	85	78	72	67	84	77	71	67	81	75	70	66	78	73	69	65	63
下方投影面積		cm ²	1.5	89	82	77	72	87	81	76	72	84	79	75	71	82	77	73	70	68
等価発光面積		cm ²	2.0	94	88	83	79	92	87	83	79	89	85	81	78	86	83	80	77	74
取付高さ	器具間隔最大限		2.5	96	92	88	84	95	91	87	84	92	88	85	82	89	86	83	81	78
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	97	93	90	87	94	91	88	85	91	89	86	84	81
Hm	1.43Hm	1.43Hm	4.0	101	98	95	92	99	96	94	91	96	94	92	90	94	92	90	88	85
			5.0	102	100	97	95	101	98	96	94	98	96	94	92	95	93	92	90	87
			7.0	104	102	100	98	102	101	99	97	100	98	97	95	97	96	94	93	90
			10.0	105	104	102	101	104	102	101	100	101	100	99	98	98	97	96	96	92

