

屋内照明器具特性	
品番 (品名)	LAMP_RF100V36W
光源	RF100V36W ×1 380.0 lm
管理番号	K0048261 (*) DN 1
BZ分類	BZ3/4.5/BZ4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	25 %	室指数	照明率 (X0.01)																ZCM	
下方光束	75 %																			
保守率	良	0.91	0.6	58	47	40	35	55	45	39	35	51	42	37	33	46	40	35	31	28
	中	0.89	0.8	67	57	50	45	64	55	49	44	59	51	46	42	54	48	43	40	36
	否	0.84	1.0	73	64	57	52	70	62	56	51	64	57	52	48	59	53	49	46	41
			1.25	79	70	64	59	75	68	62	58	69	63	58	55	63	58	55	52	46
下方投影面積		cm ²	1.5	82	75	69	64	79	72	67	63	72	67	63	59	66	62	59	56	50
	等価発光面積	cm ²	2.0	87	81	76	72	84	78	73	70	77	72	69	65	70	67	64	61	55
取付高さ	器具間隔最大限		2.5	90	85	81	77	87	82	78	74	79	76	73	70	73	70	67	65	58
	横方向 (A)	縦方向 (B)	3.0	92	88	84	80	89	84	81	78	81	78	75	73	75	72	70	68	60
Hm	0.78Hm	0.78Hm	4.0	95	91	88	85	91	88	85	82	84	81	79	77	77	75	73	71	63
			5.0	96	93	91	88	93	90	87	85	85	83	81	79	78	77	75	74	65
			7.0	98	96	94	92	94	92	90	89	87	85	84	83	80	79	78	76	68
			10.0	100	98	96	95	96	94	93	92	88	87	86	85	81	80	79	79	69

