

屋内照明器具特性

品番 (品名)	LGB85044				
光源	LED5000_70_840	x1	840.0 l m		
管理番号	K0140471(0)DB1				
BZ分類	BZ6/0.7/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%							
	上方光束		17%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%					
	下方光束		83%		床	10%				10%				10%				10%				0%				
室指数	照明率 (X0.01)																				ZCM					
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6					
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6					
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56					
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56					
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25					
	等価発光面積		c m ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.5	2.0					
取付高さ	器具間隔最大限		横方向 (A)		縦方向 (B)																					
	1.5m	2.12 m	1.86 m																							
2	2.84	2.47																								
2.5	3.53	3.08																								
3	4.24	3.69																								

