

# 屋内照明器具特性

|         |                     |          |
|---------|---------------------|----------|
| 品番 (品名) | L G W 4 5 9 4 1     |          |
| 光源      | LED2700_70_110 x1   | 110.0 lm |
| 管理番号    | K0151814 ( 0 ) DB 1 |          |
| B Z 分類  | BZ10 / 1.4 / BZ9    |          |

|        |               |                  |      |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
|--------|---------------|------------------|------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率   | 100 %         | 天井               | 80 % |      |    |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|        | 上方光束<br>81 %  |                  | 反射率  | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
| 下方光束   | 19 %          | 床                |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
| 室指数    | 照明率 ( X0.01 ) |                  |      |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     | ZCM |
| 保守率    | 良             | 0.69             | 0.6  | 43   | 31 | 24 | 19   | 37   | 28 | 21 | 17   | 27   | 20 | 16 | 12   | 18   | 13 | 10 | 8   | 1   |
|        | 中             | 0.67             | 0.8  | 51   | 40 | 32 | 27   | 44   | 35 | 28 | 24   | 32   | 26 | 21 | 17   | 22   | 17 | 14 | 11  | 2   |
|        | 否             | 0.63             | 1.0  | 57   | 46 | 39 | 33   | 49   | 41 | 34 | 29   | 36   | 30 | 25 | 22   | 24   | 20 | 17 | 14  | 3   |
| 下方投影面積 | 等価発光面積        | c m <sup>2</sup> | 1.25 | 62   | 52 | 45 | 39   | 54   | 46 | 40 | 35   | 40   | 34 | 30 | 26   | 27   | 23 | 20 | 18  | 5   |
|        |               |                  | 1.5  | 66   | 57 | 50 | 44   | 58   | 50 | 44 | 39   | 43   | 37 | 33 | 30   | 29   | 25 | 23 | 20  | 6   |
| 取付高さ   | 器具間隔最大限       |                  | 2.5  | 74   | 68 | 62 | 57   | 66   | 60 | 55 | 51   | 49   | 45 | 42 | 39   | 33   | 31 | 29 | 27  | 9   |
|        | 横方向 (A)       | 縦方向 (B)          | 3.0  | 77   | 71 | 66 | 61   | 68   | 63 | 59 | 55   | 51   | 47 | 44 | 42   | 35   | 33 | 31 | 29  | 10  |
| H m    | 0.00H m       | 0.00H m          | 4.0  | 80   | 75 | 71 | 67   | 71   | 67 | 63 | 60   | 53   | 50 | 48 | 45   | 37   | 35 | 33 | 31  | 11  |
|        |               |                  | 5.0  | 82   | 78 | 74 | 71   | 72   | 69 | 66 | 63   | 55   | 52 | 50 | 48   | 38   | 36 | 35 | 33  | 12  |
|        |               |                  | 7.0  | 84   | 81 | 78 | 75   | 75   | 72 | 70 | 67   | 57   | 55 | 53 | 51   | 39   | 38 | 37 | 36  | 13  |
|        |               |                  | 10.0 | 86   | 84 | 81 | 79   | 76   | 74 | 72 | 71   | 58   | 57 | 55 | 54   | 41   | 40 | 39 | 38  | 14  |

