

屋内照明器具特性

品番 (品名)	LGB10455														
光源	LED2700_70_300 x1 300.0 l m														
管理番号	K0150708(0)DB1														
BZ分類	BZ4/0.7/BZ3/4.5/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	7%	反射率	床	10%				10%				10%				10%				0%
下方光束	93%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.67 0.63 0.56	0.6	60	49	42	38	59	49	42	37	56	47	41	37	53	46	40	36	34	
		0.8	71	61	54	49	69	60	54	49	66	58	53	48	63	56	51	48	45	
		1.0	78	69	62	58	76	68	62	57	73	66	60	56	69	63	59	55	52	
		1.25	83	75	69	65	81	74	69	64	78	72	67	63	74	69	65	62	59	
下方投影面積	c m ²	1.5	87	80	74	70	85	78	73	69	81	76	71	68	78	73	69	66	63	
		2.0	92	86	81	77	90	84	80	76	86	81	77	74	82	78	75	72	69	
取付高さ	器具間隔最大限		2.5	94	89	85	81	92	88	84	80	88	85	81	78	85	82	79	76	73
	横方向 (A)	縦方向 (B)	3.0	96	92	88	85	94	90	87	84	90	87	84	81	87	84	81	79	75
H m	1.24 H m	1.24 H m	4.0	99	95	92	89	97	93	91	88	93	90	88	85	89	87	85	83	79
			5.0	100	97	95	92	98	95	93	91	94	92	90	88	91	89	87	85	81
			7.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	90	88	84
			10.0	103	102	100	99	101	100	98	97	97	96	95	94	94	93	92	91	86

