

屋内照明器具特性	
品番 (品名)	LGB10470
光源	LED2700_70_326 x1 326.0 lm
管理番号	K0150116(0)DB1
BZ分類	BZ3/0.7/BZ4/2.3/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	10%	床	10%				10%				10%				10%				0%	
下方光束	90%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	60	49	42	38	59	48	42	37	55	47	41	37	53	45	40	36	33
	中	0.63	0.8	69	58	51	46	67	57	50	45	63	55	49	44	60	53	47	43	41
	否	0.56	1.0	74	64	57	52	72	63	56	51	68	60	55	50	64	58	53	49	46
			1.25	79	70	63	58	77	69	62	57	73	66	60	56	69	63	58	54	51
下方投影面積			1.5	83	75	68	63	81	73	67	62	76	70	65	60	72	67	62	59	55
			2.0	88	81	75	70	85	79	74	69	81	75	71	67	76	72	68	65	61
取付高さ	器具間隔最大限		2.5	91	85	80	75	88	83	78	74	84	79	75	72	79	76	72	69	65
	横方向 (A)	縦方向 (B)	3.0	93	88	83	79	91	86	81	78	86	82	78	75	82	78	75	72	68
Hm	1.22Hm	1.22Hm	4.0	96	92	88	84	94	90	86	83	89	86	82	80	84	82	79	77	72
			5.0	98	94	91	88	95	92	89	86	91	88	85	83	86	84	82	80	75
			7.0	100	97	94	92	98	95	92	90	93	91	89	87	89	87	85	83	78
			10.0	102	99	97	96	99	97	95	94	95	93	91	90	90	89	88	86	81

