

屋内照明器具特性

品番 (品名)	LGB10416									
光源	LED2700_70_270 x1					270.0 lm				
管理番号	K0150803(0)DB1									
BZ分類	BZ2/1.1/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 8%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 92%	室指数	照明率 (X0.01)																ZCM			
保守率	良	0.67	0.6	65	55	49	45	64	55	49	44	61	53	48	44	59	52	47	43	41	
	中	0.63	0.8	74	65	59	54	72	64	58	54	69	62	57	53	66	60	56	52	50	
	否	0.56	1.0	80	71	65	61	78	70	65	60	74	68	63	59	71	66	62	58	56	
			1.25	84	77	71	67	83	76	70	66	79	73	69	65	76	71	67	64	61	
下方投影面積			1.5	88	81	76	71	86	79	75	71	82	77	73	69	79	74	71	68	64	
	等価発光面積		2.0	92	86	82	78	90	85	80	77	86	82	78	75	83	79	76	73	70	
取付高さ	器具間隔最大限		2.5	95	90	86	82	93	88	84	81	89	85	82	79	85	82	79	77	73	
	横方向 (A)	縦方向 (B)	3.0	97	92	89	85	94	91	87	84	91	87	84	82	87	84	82	80	76	
Hm	1.29Hm	1.29Hm	4.0	99	95	92	90	97	94	91	88	93	90	88	86	89	87	85	83	79	
			5.0	100	98	95	93	98	96	93	91	94	92	90	88	91	89	87	86	81	
			7.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	90	89	84	
			10.0	103	102	100	99	101	100	98	97	97	96	95	94	94	93	92	91	86	

