

屋内照明器具特性

品番 (品名)	L G W C 8 0 4 2 4																
光源	LED5000_70_469 x1 469.0 l m																
管理番号	K0160259 (0) DR 1																
B Z 分類	B Z 1 0																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	50 %	室指数	照明率 (X 0 . 0 1)																		
下方光束	50 %		Z C M																		
保守率	良 中 否 0.63 0.6 0.56	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	3		
		0.8	51	38	29	23	46	35	27	21	37	28	22	17	29	22	17	13	6		
		1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9		
		1.25	62	50	41	34	56	46	38	32	46	38	31	26	36	30	25	21	11		
下方投影面積	c m ²	1.5	66	55	47	40	60	50	43	37	49	42	35	30	39	33	28	24	14		
		2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18		
取付高さ	器具間隔最大限		2.5	76	67	60	54	69	62	55	50	57	51	46	41	46	41	37	21		
	横方向 (A)	縦方向 (B)	3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	24		
H m	0.00 H m	0.00 H m	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	44	27		
			5.0	85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30	
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	34		
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	58	57	55	37		

