

# 屋内照明器具特性

品番 (品名)	L G W C 8 1 2 9 1																
光源	LED5000_70_512 x1 512.0 l m																
管理番号	K0160258(0)DR1																
BZ分類	BZ10																

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	50%	室指数	照明率 ( X0.01 )																		
下方光束	50%		Z C M																		
保守率	良 中 否 0.63 0.6 0.56	0.6	43	30	21	16	39	27	20	14	31	22	16	11	25	17	12	9	3		
		0.8	51	38	29	23	46	34	26	21	37	28	22	17	29	22	17	13	6		
		1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9		
		1.25	62	50	41	34	56	46	38	32	46	38	31	26	36	30	25	21	11		
下方投影面積	c m <sup>2</sup>	1.5	66	55	46	40	60	50	43	36	49	41	35	30	39	33	28	24	14		
		2.0	72	62	54	48	66	57	50	44	54	47	41	37	43	38	33	29	18		
取付高さ	器具間隔最大限		2.5	76	67	60	54	69	62	55	49	57	51	46	41	46	41	37	34	21	
	横方向 (A)	縦方向 (B)	3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	37	24	
H m	0.00 H m	0.00 H m	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	44	41	27	
			5.0	85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30	
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34	
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	59	57	55	53	37	

