

屋内照明器具特性	
品番 (品名)	LGB81876
光源	LED3500_70_916 x1 916.0 lm
管理番号	K0153987(0)DB1
BZ分類	BZ8/0.7/BZ7

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	32%	床	10%				10%				10%				10%				0%	
下方光束	68%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	47	34	26	20	44	32	25	19	38	29	22	17	33	25	20	16	11	
		0.8	56	43	34	28	52	41	33	27	45	36	29	24	39	32	26	22	17	
		1.0	62	50	41	34	58	47	39	33	50	41	35	30	44	36	31	26	20	
		1.25	67	56	47	41	63	53	45	39	55	47	40	35	48	41	36	31	25	
下方投影面積	c m ²	1.5	71	61	53	46	67	57	50	44	59	51	45	40	51	45	40	35	28	
		2.0	77	68	60	54	73	64	57	51	64	57	51	46	56	50	46	42	33	
取付高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	51	59	54	50	46	37
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	64	60	55	61	57	53	50	40
1.5m	2.02m	1.93m	4.0	87	81	76	71	82	77	72	67	73	69	65	61	64	61	58	55	44
2	2.69	2.54	5.0	89	84	79	75	85	80	75	72	75	72	68	65	67	64	61	58	48
2.5	3.36	3.16	7.0	92	88	84	81	87	84	80	77	78	75	72	70	69	67	65	62	52
3	4.01	3.78	10.0	95	91	88	86	90	87	84	82	81	78	76	74	72	70	68	66	55

