

屋内照明器具特性

品番 (品名)	L G W C 8 0 4 4 2																
光源	LED2700_70_311 x1 311.0 l m																
管理番号	K0160295 (0) DR 1																
B Z 分類	B Z 1 0																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	51 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	49 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率	良 中 否 0.63 0.6 0.56	0.6	43	30	22	16	39	28	20	15	31	22	16	12	25	18	13	9	4	
		0.8	51	38	30	23	46	35	27	21	37	29	22	17	29	22	17	13	7	
		1.0	57	45	36	29	52	41	33	27	42	33	27	22	33	26	21	17	9	
		1.25	62	51	42	35	57	46	39	32	46	38	32	27	36	30	25	21	12	
下方投影面積	c m ²	1.5	67	56	47	40	61	51	43	37	49	42	36	31	39	33	29	25	14	
		2.0	72	63	55	48	66	57	50	45	54	47	42	37	43	38	34	30	18	
取付高さ	器具間隔最大限		2.5	76	68	60	54	70	62	56	50	57	51	46	42	46	41	38	34	21
	横方向 (A)	縦方向 (B)	3.0	79	71	65	59	72	65	60	54	60	54	50	46	48	44	40	37	24
H m	0.00 H m	0.00 H m	4.0	82	76	70	65	76	70	65	60	63	59	55	51	51	48	45	42	27
			5.0	85	79	74	70	78	73	69	65	65	61	58	55	53	50	47	45	30
			7.0	88	83	79	76	81	77	73	70	68	65	62	59	56	53	51	49	34
			10.0	90	87	84	81	83	80	77	75	70	68	66	64	58	56	54	53	37

