

屋内照明器具特性

品番 (品名)	L G W C 8 1 4 4 6																
光源	LED2700_70_311 x1 311.0 lm																
管理番号	K0160296(0)DR1																
BZ分類	BZ10																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %							
		床	10 %				10 %				10 %				10 %				0 %							
上方光束	50 %	室指数																								
下方光束	50 %	照明率 (X0.01)																								
		Z C M																								
保守率	良 中 否	0.63	0.6	0.6	0.6	0.6	4.3	3.0	2.2	1.6	3.9	2.8	2.0	1.5	3.2	2.3	1.6	1.2	2.5	1.8	1.3	0.9	0.4			
		0.6	0.6	0.6	0.6	0.6	5.1	3.8	3.0	2.3	4.6	3.5	2.7	2.1	3.8	2.9	2.2	1.7	3.0	2.3	1.8	1.4	0.7			
		0.56	0.6	0.6	0.6	0.6	5.7	4.5	3.6	2.9	5.2	4.1	3.3	2.7	4.2	3.3	2.7	2.2	3.3	2.7	2.1	1.7	0.9			
		0.56	0.6	0.6	0.6	0.6	6.2	5.1	4.2	3.5	5.7	4.6	3.9	3.2	4.6	3.8	3.2	2.7	3.7	3.0	2.5	2.1	1.2			
下方投影面積	c m ²	1.5	1.5	1.5	1.5	6.7	5.6	4.7	4.0	6.1	5.1	4.3	3.7	5.0	4.2	3.6	3.1	3.9	3.4	2.9	2.5	1.5				
		2.0	2.0	2.0	2.0	7.2	6.3	5.5	4.8	6.6	5.8	5.1	4.5	5.4	4.8	4.2	3.7	4.4	3.8	3.4	3.0	1.9				
取付高さ	器具間隔最大限		H m	0.00 H m	0.00 H m	2.5	2.5	2.5	2.5	7.6	6.8	6.1	5.4	7.0	6.2	5.6	5.0	5.8	5.2	4.7	4.2	4.6	4.2	3.8	3.4	2.2
	横方向 (A)	縦方向 (B)				3.0	3.0	3.0	3.0	7.9	7.1	6.5	5.9	7.2	6.6	6.0	5.4	6.0	5.5	5.0	4.6	4.9	4.5	4.1	3.8	2.4
						4.0	4.0	4.0	4.0	8.3	7.6	7.0	6.5	7.6	7.0	6.5	6.1	6.3	5.9	5.5	5.1	5.2	4.8	4.5	4.2	2.8
						5.0	5.0	5.0	5.0	8.5	7.9	7.4	7.0	7.8	7.3	6.9	6.5	6.6	6.2	5.8	5.5	5.4	5.1	4.8	4.5	3.1
						7.0	7.0	7.0	7.0	8.8	8.4	7.9	7.6	8.1	7.7	7.4	7.0	6.8	6.5	6.2	6.0	5.6	5.4	5.2	5.0	3.4
						10.0	10.0	10.0	10.0	9.0	8.7	8.4	8.1	8.4	8.1	7.8	7.5	7.1	6.8	6.6	6.4	5.9	5.7	5.5	5.3	3.7

