

| 屋内照明器具特性 | |
|----------|-----------------------------|
| 品番 (品名) | LSEB4032 |
| 光源 | LED3500_70_440 x1 440.0 l m |
| 管理番号 | K0152279(0)DB1 |
| BZ分類 | BZ6 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 23% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 77% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.63 | 0.6 | 50 | 37 | 29 | 24 | 47 | 36 | 28 | 23 | 43 | 33 | 26 | 22 | 38 | 30 | 24 | 20 | 17 |
| | 中 | 0.6 | 0.8 | 59 | 47 | 39 | 32 | 56 | 45 | 37 | 31 | 51 | 41 | 35 | 30 | 45 | 38 | 32 | 28 | 23 |
| | 否 | 0.56 | 1.0 | 65 | 54 | 45 | 39 | 62 | 51 | 44 | 38 | 56 | 47 | 41 | 35 | 50 | 43 | 38 | 33 | 28 |
| | | | 1.25 | 71 | 60 | 52 | 46 | 68 | 58 | 50 | 44 | 61 | 53 | 47 | 42 | 55 | 48 | 43 | 39 | 33 |
| 下方投影面積 | c m ² | | 1.5 | 75 | 65 | 57 | 51 | 72 | 62 | 55 | 50 | 65 | 57 | 51 | 46 | 58 | 52 | 47 | 43 | 37 |
| 等価発光面積 | c m ² | | 2.0 | 81 | 72 | 65 | 59 | 77 | 69 | 63 | 57 | 70 | 64 | 58 | 54 | 63 | 58 | 54 | 50 | 43 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 85 | 77 | 71 | 65 | 81 | 74 | 68 | 63 | 73 | 68 | 63 | 59 | 67 | 62 | 58 | 55 | 47 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 87 | 80 | 75 | 69 | 83 | 77 | 72 | 67 | 76 | 71 | 66 | 63 | 69 | 65 | 61 | 58 | 51 |
| H m | 1.41H m | 1.35H m | 4.0 | 91 | 85 | 80 | 76 | 87 | 82 | 77 | 73 | 79 | 75 | 71 | 68 | 72 | 69 | 66 | 63 | 55 |
| | | | 5.0 | 93 | 88 | 84 | 80 | 89 | 85 | 81 | 77 | 81 | 78 | 75 | 72 | 74 | 72 | 69 | 67 | 58 |
| | | | 7.0 | 95 | 92 | 88 | 85 | 91 | 88 | 85 | 82 | 84 | 81 | 79 | 76 | 77 | 75 | 73 | 71 | 62 |
| | | | 10.0 | 97 | 95 | 92 | 90 | 94 | 91 | 89 | 86 | 86 | 84 | 82 | 80 | 79 | 78 | 76 | 74 | 66 |

