

屋内照明器具特性

品番 (品名)	LGB50067														
光源	LED3500_70_1668 x1 1668.0 lm														
管理番号	K0153522(0)D 1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	3%	室指数																			
下方光束	97%	照明率 (X0.01)																			
保守率	良 0.69 中 0.67 否 0.63	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.1	3.4	3.0	2.8		
		0.8	6.6	5.4	4.6	4.1	6.4	5.4	4.6	4.1	6.1	5.2	4.5	4.0	5.8	5.0	4.4	4.0	3.7		
下方投影面積	c m ²	1.25	7.9	6.9	6.1	5.6	7.7	6.8	6.1	5.5	7.3	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.1		
		1.5	8.3	7.4	6.7	6.1	8.1	7.2	6.6	6.1	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.6		
等価発光面積	c m ²	2.0	8.8	8.1	7.5	6.9	8.6	7.9	7.4	6.9	8.3	7.7	7.2	6.8	7.9	7.4	7.0	6.7	6.3		
		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.4	8.6	8.1	7.7	7.3	8.3	7.9	7.5	7.2	6.9		
取付高さ	器具間隔最大限		3.0	9.4	8.9	8.4	7.9	9.2	8.7	8.3	7.9	8.9	8.4	8.1	7.7	8.6	8.2	7.9	7.6		
	横方向 (A)	縦方向 (B)																			
1.5m	1.93m	1.99m	4.0	9.7	9.3	8.9	8.5	9.6	9.1	8.8	8.4	9.2	8.9	8.5	8.3	8.9	8.6	8.3	8.1		
2	2.55	2.56	5.0	9.9	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.4	9.1	8.9	8.6	9.1	8.9	8.6	8.4		
2.5	3.18	3.15	7.0	10.2	9.9	9.6	9.4	10.0	9.7	9.5	9.3	9.7	9.4	9.2	9.0	9.3	9.2	9.0	8.8		
3	3.81	3.76	10.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.8	9.7	9.5	9.4	9.5	9.4	9.3	9.2		

