

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | L S E B 5 4 1 8     |           |
| 光源      | LED2700_70_420 x1   | 420.0 l m |
| 管理番号    | K0151186 ( 0 ) DB 1 |           |
| B Z 分類  | BZ4 / 0.7 / BZ3     |           |

|        |                  |          |      |      |     |     |      |      |     |     |      |      |     |     |      |      |    |    |     |     |     |
|--------|------------------|----------|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|----|----|-----|-----|-----|
| 器具効率   | 100 %            | 天井       | 80 % |      |     |     | 70 % |      |     |     | 50 % |      |     |     | 30 % |      |    |    | 0 % |     |     |
|        | 上方光束<br>0 %      |          | 反射率  | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50 | 30 | 10  | 0 % |     |
| 下方光束   | 100 %            | 床        |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |    |    |     | 0 % |     |
| 室指数    | 照明率 ( X0.01 )    |          |      |      |     |     |      |      |     |     |      |      |     |     |      |      |    |    |     |     | ZCM |
| 保守率    | 良<br>中<br>否      | 0.67     | 0.6  | 62   | 51  | 44  | 39   | 61   | 50  | 44  | 39   | 59   | 49  | 43  | 39   | 57   | 48 | 43 | 39  | 37  |     |
|        |                  | 0.63     | 0.8  | 73   | 63  | 56  | 51   | 71   | 62  | 56  | 51   | 69   | 61  | 55  | 51   | 67   | 60 | 54 | 50  | 48  |     |
|        |                  | 0.56     | 1.0  | 79   | 71  | 64  | 59   | 78   | 70  | 64  | 59   | 76   | 68  | 63  | 59   | 73   | 67 | 62 | 58  | 56  |     |
|        |                  |          | 1.25 | 85   | 77  | 71  | 67   | 84   | 77  | 71  | 67   | 81   | 75  | 70  | 66   | 79   | 73 | 69 | 66  | 64  |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 89   | 82   | 77  | 72  | 88   | 81   | 76  | 72  | 85   | 79   | 75  | 71  | 82   | 78   | 74 | 71 | 69  |     |     |
|        |                  | 2.0      | 94   | 88   | 84  | 80  | 92   | 87   | 83  | 79  | 90   | 85   | 82  | 78  | 87   | 84   | 80 | 78 | 75  |     |     |
| 取付高さ   | 器具間隔最大限          |          | 2.5  | 97   | 92  | 88  | 85   | 95   | 91  | 87  | 84   | 93   | 89  | 86  | 83   | 90   | 87 | 85 | 82  | 80  |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0  | 99   | 95  | 91  | 88   | 97   | 94  | 90  | 87   | 95   | 92  | 89  | 86   | 92   | 90 | 87 | 85  | 83  |     |
| H m    | 1.23 H m         | 1.24 H m | 4.0  | 101  | 98  | 95  | 93   | 100  | 97  | 94  | 92   | 97   | 95  | 93  | 91   | 95   | 93 | 91 | 89  | 87  |     |
|        |                  |          | 5.0  | 103  | 100 | 98  | 95   | 101  | 99  | 97  | 95   | 99   | 97  | 95  | 93   | 97   | 95 | 93 | 92  | 89  |     |
|        |                  |          | 7.0  | 104  | 102 | 101 | 99   | 103  | 101 | 100 | 98   | 101  | 99  | 98  | 96   | 98   | 97 | 96 | 95  | 92  |     |
|        |                  |          | 10.0 | 105  | 104 | 103 | 102  | 104  | 103 | 102 | 101  | 102  | 101 | 100 | 99   | 100  | 99 | 98 | 97  | 94  |     |

