

屋内照明器具特性

品番 (品名)	L S E B 9 0 1 7														
光源	LED2700_70_535 x1 535.0 l m														
管理番号	K0153522(0)D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	3 %																			
下方光束	97 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.69 中 0.67 否 0.63	0.6	56	44	36	31	55	43	36	30	52	42	35	30	49	41	34	30	28	
		0.8	66	54	46	41	64	54	46	41	61	52	45	40	58	50	44	40	37	
		1.0	73	62	54	48	71	61	53	48	67	59	52	47	64	57	51	47	44	
		1.25	79	69	61	56	77	68	61	55	73	65	59	54	70	63	58	54	51	
下方投影面積	c m ²	1.5	83	74	67	61	81	72	66	61	77	70	64	60	74	68	63	59	56	
		2.0	88	81	75	69	86	79	74	69	83	77	72	68	79	74	70	67	63	
		2.5	92	85	80	75	90	84	79	74	86	81	77	73	83	79	75	72	69	
取付高さ	器具間隔最大限		3.0	94	89	84	79	92	87	83	79	89	84	81	77	86	82	79	76	72
	横方向 (A)	縦方向 (B)																		
1.5m	1.9 m	1.86 m	4.0	97	93	89	85	96	91	88	84	92	89	85	83	89	86	83	81	77
2	2.54	2.48	5.0	99	96	92	89	98	94	91	88	94	91	89	86	91	89	86	84	81
2.5	3.17	3.09	7.0	102	99	96	94	100	97	95	93	97	94	92	90	93	92	90	88	85
3	3.81	3.71	10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	92	88

