

屋内照明器具特性

品番 (品名)	LSEB9020														
光源	LED2700_70_1070 x1 1070.0 1m														
管理番号	K0153522(0)D 1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	3%																				
下方光束	97%																				
		室指数	照明率 (X0.01) ZCM																		
保守率	良 0.69 中 0.67 否 0.63	0.6	56	44	36	31	55	43	36	30	52	42	35	30	49	41	34	30	28		
		0.8	66	54	46	41	64	54	46	41	61	52	45	40	58	50	44	40	37		
		1.0	73	62	54	48	71	61	53	48	67	59	52	47	64	57	51	47	44		
		1.25	79	69	61	56	77	68	61	55	73	65	59	54	70	63	58	54	51		
下方投影面積	c m ²	1.5	83	74	67	61	81	72	66	61	77	70	64	60	74	68	63	59	56		
		2.0	88	81	75	69	86	79	74	69	83	77	72	68	79	74	70	67	63		
		2.5	92	85	80	75	90	84	79	74	86	81	77	73	83	79	75	72	69		
取付高さ	器具間隔最大限		3.0	94	89	84	79	92	87	83	79	89	84	81	77	86	82	79	76	72	
	横方向 (A)	縦方向 (B)	4.0	97	93	89	85	96	91	88	84	92	89	85	83	89	86	83	81	77	
1.5m	1.91m	1.9m	5.0	99	96	92	89	98	94	91	88	94	91	89	86	91	89	86	84	81	
2	2.54	2.51	7.0	102	99	96	94	100	97	95	93	97	94	92	90	93	92	90	88	85	
2.5	3.19	3.11	10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	92	88	
3	3.81	3.71																			

