

# 屋内照明器具特性

品番 (品名)	LSEB5805															
光源	LED2700_70_685 x1 685.0 lm															
管理番号	K0151698(0)D 1															
BZ分類	BZ3															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 ( X0.01 ) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.67	0.6	64	54	47	42	63	53	47	42	61	52	47	42	59	51	46	42	40	
		0.63	0.8	74	65	58	54	73	64	58	54	71	63	58	53	69	62	57	53	51	
			1.0	81	72	66	62	80	72	66	61	77	70	65	61	75	69	64	61	59	
		0.56	1.25	86	79	73	69	85	78	73	68	82	76	72	68	80	75	71	67	66	
下方投影面積	c m <sup>2</sup>	1.5	90	83	78	74	88	82	77	73	86	81	76	73	83	79	75	72	70		
		2.0	94	89	84	81	93	88	84	80	90	86	83	79	88	84	81	79	77		
取付高さ	器具間隔最大限		2.5	97	93	89	85	96	92	88	85	93	90	87	84	91	88	85	83	81	
	横方向 (A)	縦方向 (B)	3.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	86	83	
H m	1.15 H m	1.15 H m	4.0	101	98	95	93	100	97	95	92	98	95	93	91	95	93	91	90	87	
			5.0	103	100	98	96	102	99	97	95	99	97	95	94	97	95	94	92	90	
			7.0	104	102	101	99	103	101	100	98	101	99	98	97	98	97	96	95	92	
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	94	

