

屋内照明器具特性

品番 (品名)	LGB10833														
光源	LLD3000CU1 x1 795.0 lm														
管理番号	K0179076(0)DR1														
BZ分類	BZ5/0.7/BZ4/1.8/BZ5														

器具効率	96%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	7% 89%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	55	43	36	31	53	42	36	31	50	41	35	30	47	39	34	30	28		
		0.8	64	53	46	41	62	52	46	40	59	50	44	40	56	49	43	39	36		
		1.0	70	60	53	48	68	59	52	47	65	57	51	46	61	55	50	46	43		
		1.25	76	67	60	55	73	65	59	54	70	63	57	53	66	60	56	52	49		
下方投影面積 等価発光面積	c m ² c m ²	1.5	79	71	65	60	77	70	64	59	73	67	62	58	70	64	60	56	53		
		2.0	84	77	72	67	82	76	70	66	78	73	68	64	74	70	66	63	59		
取付 高さ	器具間隔最大限		2.5	87	81	76	72	85	80	75	71	81	77	73	69	77	74	70	67	63	
	横方向 (A) 縦方向 (B)	3.0	90	84	80	76	87	83	78	75	83	79	76	73	80	76	73	71	67		
H m	1.29 H m	1.29 H m	4.0	92	88	84	81	90	86	83	80	86	83	80	77	82	80	77	75	71	
			5.0	94	91	87	84	92	89	86	83	88	85	83	80	84	82	80	78	74	
			7.0	96	93	91	89	94	92	89	87	90	88	86	84	86	85	83	82	77	
			10.0	98	96	94	92	96	94	92	90	92	90	89	87	88	87	86	85	80	

