

屋内照明器具特性	
品番 (品名)	L S E W4 0 3 7
光源	LED5000_70_540 ×1 540.0 l m
管理番号	K0160257 ( 0 ) DR 1
B Z 分類	BZ10

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	3
	中	0.6	0.8	51	38	29	23	46	34	27	21	37	28	22	17	29	22	17	13	6
	否	0.56	1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9
			1.25	62	50	41	34	56	46	38	32	46	38	31	26	36	30	25	21	11
下方投影面積		cm <sup>2</sup>	1.5	66	55	47	40	60	50	43	36	49	41	35	30	39	33	28	24	14
等価発光面積		cm <sup>2</sup>	2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18
取付高さ	器具間隔最大限		2.5	76	67	60	54	69	62	55	49	57	51	46	41	46	41	37	34	21
	横方向 (A)	縦方向 (B)	3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	37	24
H <sub>m</sub>	0.00H <sub>m</sub>	0.00H <sub>m</sub>	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	44	41	27
			5.0	85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	58	57	55	53	37

