

屋内照明器具特性	
品番 (品名)	XLY090EL
光源	LED3000_85_1090 ×1 1090.0 lm
管理番号	K0155409 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		6 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		94 %																							
保守率		良 中 否	0.83	0.6	55	42	34	29	53	41	34	28	50	40	33	28	47	38	32	28	25				
			0.81	0.8	64	52	44	38	62	51	44	38	59	49	43	37	56	48	41	37	34				
			0.77	1.0	71	60	52	46	69	58	51	45	65	56	49	44	62	54	48	43	41				
				1.25	77	66	59	53	75	65	58	52	71	62	56	51	67	60	55	50	47				
下方投影面積		cm ²		1.5	81	71	64	58	79	70	63	58	75	67	61	56	71	65	59	55	52				
				2.0	86	78	72	66	84	77	71	66	80	74	69	64	76	71	67	63	59				
取付高さ	器具間隔最大限			2.5	90	83	77	72	88	81	76	71	84	78	74	69	80	75	71	68	64				
	横方向 (A) 縦方向 (B)			3.0	92	86	81	76	90	85	80	75	86	81	77	74	82	78	75	72	68				
1.5m	1.96 m	2 m		4.0	96	91	86	82	94	89	85	81	90	86	82	79	86	83	80	77	73				
2	2.6	2.58		5.0	98	94	90	86	96	92	88	85	92	88	85	83	88	85	83	80	76				
2.5	3.24	3.18		7.0	100	97	94	91	98	95	92	90	94	92	89	87	91	89	87	85	81				
3	3.87	3.78		10.0	102	100	97	95	100	98	96	94	96	94	93	91	93	91	90	88	84				

