

屋内照明器具特性	
品番 (品名)	XLY090HP
光源	LED2700_85_2050 ×1 2050.0 lm
管理番号	K0155408 (0) DB 1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.83	0.6	54	42	34	28	53	41	33	28	49	39	32	27	47	38	32	27	25	
			0.81	0.8	64	52	44	38	62	51	43	38	58	49	42	37	55	47	41	36	33	
			0.77	1.0	70	59	51	45	68	58	50	44	64	55	49	44	61	53	47	43	40	
				1.25	76	66	58	52	74	65	57	52	70	62	56	50	66	59	54	49	46	
下方投影面積		cm ²		1.5	80	71	63	58	78	69	62	57	74	66	61	56	70	64	59	54	51	
			等価発光面積	cm ²	2.0	86	78	71	66	84	76	70	65	79	73	68	63	75	70	66	62	58
取付 高さ	器具間隔最大限			2.5	90	83	77	72	87	81	75	71	83	78	73	69	79	74	70	67	63	
	横方向 (A)		縦方向 (B)	3.0	92	86	81	76	90	84	79	75	86	81	77	73	82	78	74	71	67	
1.5m	1.98 m	2.02 m	4.0	95	90	86	82	93	89	84	81	89	85	82	78	85	82	79	76	72		
2	2.62	2.6	5.0	97	93	89	86	95	91	88	85	91	88	85	82	87	85	82	80	75		
2.5	3.25	3.21	7.0	100	97	94	91	98	95	92	89	94	91	89	87	90	88	86	84	79		
3	3.89	3.81	10.0	102	99	97	95	100	98	95	93	96	94	92	90	92	90	89	88	83		

