

屋内照明器具特性

品番 (品名)	NNN5 1 1 5 1 S	
光源	LED2700_70_325 ×1	325.0 lm
管理番号	K0152720(0)DB1	
BZ分類	BZ1/0.7/BZ2/3.5/BZ3	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 11%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	89%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.63	0.6	0.6	69	60	55	51	68	59	54	50	65	58	53	50	62	56	52	49	47
	中 0.6	0.6	0.8	77	69	63	59	75	68	62	58	72	65	61	57	69	63	59	56	54
	否 0.56	0.6	1.0	82	74	69	65	80	73	68	64	76	70	66	63	73	68	64	61	58
下方投影面積 等価発光面積	cm ²	cm ²	1.25	86	79	74	70	84	78	73	69	80	75	71	68	76	72	69	66	63
			1.5	89	83	78	74	87	81	77	73	83	78	74	71	79	75	72	69	66
取付高さ Hm	器具間隔最大限		2.5	95	91	87	84	93	89	85	83	89	85	82	80	84	82	79	77	73
	横方向 (A)	縦方向 (B)	3.0	97	93	90	87	95	91	88	85	90	87	85	82	86	84	81	80	75
Hm	0.59Hm	0.59Hm	4.0	99	96	93	91	97	94	91	89	92	90	88	86	88	86	84	83	78
			5.0	100	98	95	93	98	96	93	91	93	91	90	88	89	87	86	85	79
			7.0	102	100	98	96	100	98	96	94	95	93	92	91	91	89	88	87	82
			10.0	103	102	100	99	101	99	98	97	96	95	94	93	92	91	90	89	83

