

屋内照明器具特性	
品番 (品名)	NNN5 1 1 5 2 S
光源	LED2700_70_540 ×1 540.0 l m
管理番号	K0152721 (0) DB 1
B Z 分類	BZ9 / 0.7 / BZ8 / 1.8 / BZ7

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	16 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	84 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	4.6	3.2	2.4	1.7	4.4	3.1	2.3	1.7	4.0	2.9	2.1	1.6	3.6	2.6	2.0	1.5	1.2
	中	0.6	0.8	5.5	4.2	3.2	2.5	5.3	4.0	3.1	2.5	4.8	3.7	2.9	2.3	4.3	3.4	2.7	2.2	1.8
	否	0.56	1.0	6.2	4.8	3.9	3.2	5.9	4.7	3.8	3.1	5.3	4.3	3.5	2.9	4.8	3.9	3.3	2.7	2.3
			1.25	6.8	5.5	4.6	3.9	6.5	5.3	4.4	3.8	5.9	4.9	4.2	3.6	5.3	4.5	3.9	3.4	2.9
下方投影面積		cm ²	1.5	7.2	6.1	5.2	4.4	6.9	5.8	5.0	4.3	6.3	5.4	4.7	4.1	5.7	5.0	4.4	3.8	3.3
等価発光面積		cm ²	2.0	7.8	6.8	6.0	5.3	7.5	6.6	5.8	5.2	6.9	6.1	5.4	4.9	6.3	5.6	5.1	4.6	4.0
取付高さ	器具間隔最大限		2.5	8.3	7.4	6.6	6.0	7.9	7.1	6.4	5.8	7.3	6.6	6.0	5.5	6.7	6.1	5.6	5.2	4.6
	横方向 (A)	縦方向 (B)	3.0	8.6	7.8	7.1	6.5	8.2	7.5	6.9	6.3	7.6	7.0	6.4	5.9	7.0	6.5	6.0	5.6	5.0
H _m	1.99H _m	1.99H _m	4.0	9.0	8.3	7.7	7.2	8.6	8.0	7.5	7.0	8.0	7.5	7.0	6.6	7.4	7.0	6.6	6.2	5.6
			5.0	9.2	8.7	8.1	7.7	8.9	8.4	7.9	7.5	8.3	7.8	7.4	7.1	7.7	7.3	7.0	6.7	6.0
			7.0	9.5	9.1	8.7	8.3	9.2	8.8	8.4	8.1	8.6	8.2	7.9	7.6	8.0	7.7	7.5	7.2	6.5
			10.0	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	8.9	8.6	8.3	8.1	8.3	8.1	7.9	7.7	7.0

