

屋内照明器具特性

品番 (品名)	NNN1 2 2 9 6									
光源	LED4000_70_890 ×1					890.0 l m				
管理番号	K0146635 (0) DB 1									
B Z 分類	B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		20 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		80 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.69	0.6	51	38	30	25	48	37	29	24	44	34	28	23	40	32	26	22	18	
	中	0.67	0.8	60	48	39	33	57	46	38	33	52	43	36	31	47	39	34	29	25	
	否	0.63	1.0	66	55	46	40	63	53	45	39	57	49	42	37	52	45	39	35	30	
	下方投影面積	c m ²		1.25	72	61	53	47	69	59	51	46	63	54	48	43	57	50	45	41	35
等価発光面積	c m ²		1.5	76	66	58	52	73	64	56	51	66	59	53	48	60	54	49	45	39	
	c m ²		2.0	82	73	66	60	78	70	64	58	71	65	60	55	65	60	56	52	46	
取付高さ	器具間隔最大限		2.5	85	78	71	66	82	75	69	64	75	69	64	60	69	64	60	56	50	
	横方向 (A)	縦方向 (B)	3.0	88	81	75	70	84	78	73	68	77	72	68	64	71	67	63	60	53	
1.5m	2.1 m	1.87 m	4.0	91	86	81	76	88	83	78	74	81	77	73	70	74	71	68	65	58	
2	2.81	2.48	5.0	93	89	84	80	90	86	82	78	83	79	76	73	77	74	71	69	61	
2.5	3.53	3.09	7.0	96	92	89	86	92	89	86	83	86	83	80	78	79	77	75	73	65	
3	4.23	3.71	10.0	98	95	93	90	95	92	90	87	88	86	84	82	81	80	78	77	68	

