

屋内照明器具特性	
品番 (品名)	XLW451ZENZ
光源	LED5000_85_4710 ×1 4710.0 lm
管理番号	K0143449 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z
保守率		良 中 否	0.83	0.6	56	43	36	30	54	43	35	30	51	41	34	30	49	40	34	29	27				
			0.81	0.8	66	54	46	40	64	53	45	40	60	51	44	39	57	49	43	39	36				
			0.77	1.0	72	61	53	48	70	60	53	47	67	58	51	46	63	56	50	46	43				
				1.25	78	68	61	55	76	67	60	54	72	64	58	53	69	62	57	53	50				
下方投影面積		cm ²	1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	54					
			2.0	88	80	74	69	86	78	73	68	82	76	71	66	78	73	69	65	62					
等価発光面積		cm ²	2.5	91	84	79	74	89	83	78	73	85	80	76	72	81	77	73	70	67					
			3.0	94	88	83	78	91	86	82	77	88	83	79	76	84	80	77	74	70					
1.5m		1.98 m	2.18 m	4.0	97	92	88	84	95	90	87	83	91	87	84	81	87	84	82	79	75				
2		2.61	2.71	5.0	99	95	91	88	97	93	90	87	93	90	87	85	89	87	85	82	78				
2.5		3.25	3.28	7.0	101	98	95	93	99	96	94	91	95	93	91	89	92	90	88	86	82				
3		3.88	3.86	10.0	103	100	98	96	101	99	97	95	97	96	94	92	94	92	91	90	86				

