

屋内照明器具特性	
品番 (品名)	XLX190AEV
光源	LED3500_85_8380 x1 8380.0 lm
管理番号	K0154867(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	100%	室指数	照明率 (X0.01)																				ZCM
保守率	良 0.81 中 0.77 否 0.68	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.1	5.3	4.2	3.5	3.0	5.0	4.1	3.5	3.0	2.8				
		0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.6	4.1	6.2	5.3	4.6	4.1	6.0	5.1	4.5	4.0	3.8				
		1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.4	4.8	6.8	6.0	5.3	4.8	6.6	5.8	5.2	4.7	4.5				
		1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.6	7.4	6.6	6.0	5.5	7.1	6.5	5.9	5.5	5.2				
下方投影面積	cm ²	1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.7	6.1	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.0	5.8				
		2.0	8.9	8.1	7.5	7.0	8.7	8.0	7.4	7.0	8.4	7.8	7.3	6.9	8.1	7.6	7.2	6.8	6.6				
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.6	9.1	8.5	8.0	7.5	8.8	8.3	7.8	7.4	8.5	8.1	7.7	7.3	7.1			
	横方向 (A)	縦方向 (B)	3.0	9.5	8.9	8.4	8.0	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.5			
1.5m	1.92m	1.93m	4.0	9.8	9.4	9.0	8.6	9.7	9.3	8.9	8.6	9.4	9.0	8.7	8.4	9.1	8.8	8.5	8.3	8.0			
2	2.53	2.54	5.0	10.0	9.6	9.3	9.0	9.9	9.5	9.2	8.9	9.6	9.3	9.0	8.8	9.3	9.1	8.9	8.7	8.4			
2.5	3.13	3.14	7.0	10.2	10.0	9.7	9.5	10.1	9.9	9.6	9.4	9.8	9.6	9.4	9.2	9.6	9.4	9.2	9.1	8.8			
3	3.76	3.77	10.0	10.4	10.2	10.0	9.9	10.3	10.1	9.9	9.8	10.0	9.9	9.7	9.6	9.8	9.7	9.5	9.4	9.1			

