

屋内照明器具特性

品番 (品名)	XLW4 4 2 AENZ									
光源	LED5000_85_3830 x1					3830.0 lm				
管理番号	K0141081 (6) DB1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	6 %																			
下方光束	94 %																			
室指数	照明率 (X0.01)																ZCM			
保守率	良	0.83	0.6	55	42	34	29	53	42	34	29	50	40	33	28	47	39	32	28	25
	中	0.81	0.8	64	53	45	39	63	52	44	38	59	50	43	38	56	48	42	37	34
	否	0.77	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	48	44	41
			1.25	77	67	59	53	75	65	58	53	71	63	57	52	67	60	55	50	47
下方投影面積		cm ²	1.5	81	72	64	59	79	70	63	58	75	67	62	57	71	65	60	56	52
等価発光面積		cm ²	2.0	87	79	72	67	84	77	71	66	80	74	69	65	76	71	67	63	59
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	84	78	74	70	80	75	72	68	64
	横方向 (A)	縦方向 (B)	3.0	93	87	81	77	90	85	80	76	86	82	78	74	82	79	75	72	68
1.5m	1.97 m	2.09 m	4.0	96	91	87	83	94	89	85	82	90	86	83	79	86	83	80	77	73
2	2.6	2.65	5.0	98	94	90	87	96	92	89	85	92	89	86	83	88	85	83	81	77
2.5	3.24	3.22	7.0	100	97	94	92	98	95	93	90	94	92	90	88	91	89	87	85	81
3	3.86	3.81	10.0	102	100	98	96	100	98	96	94	96	95	93	91	93	91	90	88	84

