

# 屋内照明器具特性

品番 (品名)	XLY120EW									
光源	LED4000_85_1380 x1					1380.0 lm				
管理番号	K0155409(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	6%																			
下方光束	94%																			
室指数	照明率 ( X0.01 )																ZCM			
保守率	良 中 否	0.83	0.6	5.5	4.2	3.4	2.9	5.3	4.1	3.4	2.8	5.0	4.0	3.3	2.8	4.7	3.8	3.2	2.8	2.5
		0.81	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.4	3.8	5.9	4.9	4.3	3.7	5.6	4.8	4.1	3.7	3.4
		0.77	1.0	7.1	6.0	5.2	4.6	6.9	5.8	5.1	4.5	6.5	5.6	4.9	4.4	6.2	5.4	4.8	4.3	4.1
			1.25	7.7	6.6	5.9	5.3	7.5	6.5	5.8	5.2	7.1	6.2	5.6	5.1	6.7	6.0	5.5	5.0	4.7
下方投影面積		cm <sup>2</sup>																		
等価発光面積		cm <sup>2</sup>																		
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
1.5m	1.98m	2.12m	4.0	9.6	9.1	8.6	8.2	9.4	8.9	8.5	8.1	9.0	8.6	8.2	7.9	8.6	8.3	8.0	7.7	7.3
2	2.62	2.67	5.0	9.8	9.4	9.0	8.6	9.6	9.2	8.8	8.5	9.2	8.8	8.5	8.3	8.8	8.5	8.3	8.0	7.6
2.5	3.26	3.24	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	9.0	9.4	9.2	8.9	8.7	9.1	8.9	8.7	8.5	8.1
3	3.89	3.84	10.0	10.2	10.0	9.7	9.5	10.0	9.8	9.6	9.4	9.6	9.4	9.3	9.1	9.3	9.1	9.0	8.8	8.4

