

屋内照明器具特性

品番 (品名)	FYY76240															
光源	LED4000_85_1830 x1 1830.0 lm															
管理番号	K0159145(0)DR1															
BZ分類	BZ7/0.9/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	5%	反射率	床	10%				10%				10%				10%				0%
下方光束	95%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.83	0.6	50	36	27	21	48	35	27	21	45	34	26	20	42	32	25	20	18
		0.81	0.8	59	46	37	30	57	45	36	30	54	43	35	29	50	41	34	29	26
		0.77	1.0	66	53	44	37	64	52	43	37	60	50	42	36	56	47	41	35	32
			1.25	72	60	51	44	70	59	50	44	66	56	49	43	62	54	47	42	39
下方投影面積			1.5	77	66	57	50	74	64	56	50	70	61	54	49	66	59	53	48	44
等価発光面積			2.0	83	73	66	59	80	72	65	59	76	69	62	57	72	66	60	56	52
取付高さ	器具間隔最大限		2.5	87	79	72	66	85	77	70	65	80	74	68	63	76	71	66	62	58
	横方向 (A)	縦方向 (B)	3.0	90	82	76	70	87	81	75	70	83	77	72	68	79	74	70	66	62
1.5m	0	2.2m	4.0	93	87	82	77	91	86	81	76	87	82	78	74	83	79	76	72	68
2	0	2.78	5.0	96	91	86	82	94	89	85	81	90	86	82	79	86	82	79	76	72
2.5	0	3.39	7.0	99	95	91	88	97	93	90	86	93	90	87	84	89	86	84	82	78
3	0	4.02	10.0	101	98	95	92	99	96	94	91	95	93	91	89	92	90	88	86	82

