

# 屋内照明器具特性

品番 (品名)	FYY75253															
光源	LED5000_85_985 x1 985.0 lm															
管理番号	K0159145(0)DR1															
BZ分類	BZ7/0.9/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数	照明率 ( X0.01) ZCM																		
下方光束	95%																				
保守率	良 中 否	0.83	0.6	50	36	27	21	48	35	27	21	45	34	26	20	42	32	25	20	18	
		0.81	0.8	59	46	37	30	57	45	36	30	54	43	35	29	50	41	34	29	26	
		0.77	1.0	66	53	44	37	64	52	43	37	60	50	42	36	56	47	41	35	32	
			1.25	72	60	51	44	70	59	50	44	66	56	49	43	62	54	47	42	39	
下方投影面積	c m <sup>2</sup>	1.5	77	66	57	50	74	64	56	50	70	61	54	49	66	59	53	48	44		
		2.0	83	73	66	59	80	72	65	59	76	69	62	57	72	66	60	56	52		
取付高さ	器具間隔最大限		2.5	87	79	72	66	85	77	70	65	80	74	68	63	76	71	66	62	58	
	横方向 (A)	縦方向 (B)	3.0	90	82	76	70	87	81	75	70	83	77	72	68	79	74	70	66	62	
1.5m	0	2.01m	4.0	93	87	82	77	91	86	81	76	87	82	78	74	83	79	76	72	68	
2	0	2.66	5.0	96	91	86	82	94	89	85	81	90	86	82	79	86	82	79	76	72	
2.5	0	3.31	7.0	99	95	91	88	97	93	90	86	93	90	87	84	89	86	84	82	78	
3	0	3.93	10.0	101	98	95	92	99	96	94	91	95	93	91	89	92	90	88	86	82	

