

# 屋内照明器具特性

品番 (品名)	FYY75253															
光源	LED5000_85_985 x1 985.0 lm															
管理番号	K0159145(0)DR1															
BZ分類	BZ7/0.9/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	5%																			
下方光束	95%																			
室指数	照明率 ( X0.01) ZCM																			
保守率	良 中 否	0.83	0.6	50	36	27	21	48	35	27	21	45	34	26	20	42	32	25	20	18
		0.81	0.8	59	46	37	30	57	45	36	30	54	43	35	29	50	41	34	29	26
		0.77	1.0	66	53	44	37	64	52	43	37	60	50	42	36	56	47	41	35	32
			1.25	72	60	51	44	70	59	50	44	66	56	49	43	62	54	47	42	39
下方投影面積		cm <sup>2</sup>																		
等価発光面積		cm <sup>2</sup>																		
取付高さ	器具間隔最大限		2.5	87	79	72	66	85	77	70	65	80	74	68	63	76	71	66	62	58
	横方向 (A)	縦方向 (B)																		
1.5m	0	2.01m	4.0	93	87	82	77	91	86	81	76	87	82	78	74	83	79	76	72	68
2	0	2.66	5.0	96	91	86	82	94	89	85	81	90	86	82	79	86	82	79	76	72
2.5	0	3.31	7.0	99	95	91	88	97	93	90	86	93	90	87	84	89	86	84	82	78
3	0	3.93	10.0	101	98	95	92	99	96	94	91	95	93	91	89	92	90	88	86	82

