

屋内照明器具特性

品番 (品名)	FYY75202															
光源	LED3500_85_915 x1 915.0 lm															
管理番号	K0159145(0)DR1															
BZ分類	BZ7/0.9/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数																			
下方光束	95%	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.83	0.6	50	36	27	21	48	35	27	21	45	34	26	20	42	32	25	20	18	
		0.81	0.8	59	46	37	30	57	45	36	30	54	43	35	29	50	41	34	29	26	
		0.77	1.0	66	53	44	37	64	52	43	37	60	50	42	36	56	47	41	35	32	
			1.25	72	60	51	44	70	59	50	44	66	56	49	43	62	54	47	42	39	
下方投影面積	c m ²	1.5	77	66	57	50	74	64	56	50	70	61	54	49	66	59	53	48	44		
		2.0	83	73	66	59	80	72	65	59	76	69	62	57	72	66	60	56	52		
取付高さ	器具間隔最大限		2.5	87	79	72	66	85	77	70	65	80	74	68	63	76	71	66	62	58	
	横方向 (A)	縦方向 (B)	3.0	90	82	76	70	87	81	75	70	83	77	72	68	79	74	70	66	62	
1.5m	0 m	2.01 m	4.0	93	87	82	77	91	86	81	76	87	82	78	74	83	79	76	72	68	
2	0	2.66	5.0	96	91	86	82	94	89	85	81	90	86	82	79	86	82	79	76	72	
2.5	0	3.31	7.0	99	95	91	88	97	93	90	86	93	90	87	84	89	86	84	82	78	
3	0	3.93	10.0	101	98	95	92	99	96	94	91	95	93	91	89	92	90	88	86	82	

