

屋内照明器具特性	
品番 (品名)	FYY75232
光源	LED3000_85_910 x1 910.0 lm
管理番号	K0159145(0)DR1
BZ分類	BZ7/0.9/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	5%	床	10%				10%				10%				10%				0%	
下方光束	95%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	50	36	27	21	48	35	27	21	45	34	26	20	42	32	25	20	18
	中	0.81	0.8	59	46	37	30	57	45	36	30	54	43	35	29	50	41	34	29	26
	否	0.77	1.0	66	53	44	37	64	52	43	37	60	50	42	36	56	47	41	35	32
			1.25	72	60	51	44	70	59	50	44	66	56	49	43	62	54	47	42	39
下方投影面積		cm ²	1.5	77	66	57	50	74	64	56	50	70	61	54	49	66	59	53	48	44
等価発光面積		cm ²	2.0	83	73	66	59	80	72	65	59	76	69	62	57	72	66	60	56	52
取付高さ	器具間隔最大限		2.5	87	79	72	66	85	77	70	65	80	74	68	63	76	71	66	62	58
	横方向 (A)	縦方向 (B)	3.0	90	82	76	70	87	81	75	70	83	77	72	68	79	74	70	66	62
1.5m	0	2.01m	4.0	93	87	82	77	91	86	81	76	87	82	78	74	83	79	76	72	68
2	0	2.66	5.0	96	91	86	82	94	89	85	81	90	86	82	79	86	82	79	76	72
2.5	0	3.31	7.0	99	95	91	88	97	93	90	86	93	90	87	84	89	86	84	82	78
3	0	3.93	10.0	101	98	95	92	99	96	94	91	95	93	91	89	92	90	88	86	82

