

屋内照明器具特性

品番 (品名)	LGBX10000														
光源	LED2700_70_510 x1 510.0 lm														
管理番号	K0152467(0)DB1														
BZ分類	BZ6														

器具効率	94%	天井	80%				70%				50%				30%				0%		
	上方光束		25%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		69%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.67	0.6	48	36	29	24	45	35	28	23	40	32	26	22	36	29	24	20	17	
	中	0.63	0.8	56	45	38	32	53	43	36	31	48	40	34	29	43	36	31	27	23	
	否	0.56	1.0	62	52	44	38	59	49	42	37	53	45	39	35	47	41	36	32	27	
			1.25	67	58	50	45	64	55	48	43	57	50	45	40	52	46	41	37	32	
下方投影面積			1.5	71	62	55	50	67	59	53	48	61	54	49	45	55	49	45	41	35	
			2.0	76	68	62	57	72	65	60	55	65	60	55	51	59	54	50	47	40	
取付高さ	器具間隔最大限		2.5	79	73	67	62	76	69	64	60	68	63	59	55	62	58	54	51	44	
	横方向 (A)	縦方向 (B)	3.0	82	76	71	66	78	72	68	64	71	66	62	59	64	60	57	54	47	
Hm	1.46Hm	1.46Hm	4.0	85	80	75	72	81	76	72	69	74	70	67	64	67	64	61	59	51	
			5.0	87	82	79	75	83	79	76	72	75	72	70	67	69	66	64	62	53	
			7.0	89	86	83	80	85	82	79	77	78	75	73	71	71	69	67	65	57	
			10.0	91	88	86	84	87	85	83	81	80	78	76	74	73	71	70	68	59	

