

# 屋内照明器具特性

|         |                |    |       |    |  |
|---------|----------------|----|-------|----|--|
| 品番 (品名) | LGB51636       |    |       |    |  |
| 光源      | LED5000_70_865 | x1 | 865.0 | lm |  |
| 管理番号    | K0160460(4)DB1 |    |       |    |  |
| BZ分類    | BZ5            |    |       |    |  |

| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |    | 50% |     |    |    | 30% |    |    |    | 0%  |    |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|-----|----|----|----|-----|----|
|        |         |                 | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70  | 50 | 30 | 10  | 70 | 50 | 30 | 10  | 0% |
| 上方光束   | 0%      | 床               | 10%           |     |     |     | 10% |     |     |    | 10% |     |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%    | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |    |     |     |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.69            | 0.6           | 57  | 45  | 37  | 31  | 55  | 44  | 36 | 31  | 53  | 43 | 36 | 31  | 51 | 42 | 36 | 31  | 29 |
|        | 中       | 0.67            | 0.8           | 67  | 55  | 47  | 42  | 65  | 55  | 47 | 42  | 63  | 53 | 46 | 41  | 60 | 52 | 46 | 41  | 39 |
|        | 否       | 0.63            | 1.0           | 74  | 63  | 55  | 49  | 72  | 62  | 55 | 49  | 69  | 60 | 54 | 49  | 66 | 59 | 53 | 48  | 46 |
|        |         |                 | 1.25          | 80  | 70  | 63  | 57  | 78  | 69  | 62 | 57  | 75  | 67 | 61 | 56  | 72 | 65 | 60 | 56  | 53 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 84  | 75  | 68  | 63  | 82  | 74  | 67 | 62  | 79  | 72 | 66 | 62  | 76 | 70 | 65 | 61  | 59 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 89  | 82  | 76  | 71  | 88  | 81  | 75 | 71  | 85  | 79 | 74 | 70  | 82 | 77 | 73 | 69  | 67 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 93  | 87  | 81  | 77  | 91  | 86  | 81 | 76  | 88  | 83 | 79 | 75  | 85 | 81 | 78 | 74  | 72 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 95  | 90  | 85  | 81  | 94  | 89  | 84 | 81  | 91  | 87 | 83 | 79  | 88 | 84 | 81 | 78  | 76 |
| Hm     | 1.27Hm  | 1.27Hm          | 4.0           | 99  | 94  | 90  | 87  | 97  | 93  | 89 | 86  | 94  | 91 | 88 | 85  | 91 | 89 | 86 | 84  | 81 |
|        |         |                 | 5.0           | 100 | 97  | 94  | 91  | 99  | 96  | 93 | 90  | 96  | 93 | 91 | 88  | 94 | 91 | 89 | 87  | 84 |
|        |         |                 | 7.0           | 103 | 100 | 97  | 95  | 101 | 99  | 96 | 94  | 99  | 96 | 95 | 93  | 96 | 94 | 93 | 91  | 88 |
|        |         |                 | 10.0          | 104 | 102 | 101 | 99  | 103 | 101 | 99 | 98  | 100 | 99 | 97 | 96  | 98 | 97 | 95 | 94  | 91 |

