

屋内照明器具特性

品番 (品名)	LGB15542															
光源	LED3500_70_485 x1 485.0 lm															
管理番号	K0151381(0)DB1															
BZ分類	BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	4% 96%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	56	43	35	30	54	42	35	30	51	41	34	29	49	40	34	29	27		
		0.8	65	54	46	40	64	53	45	40	61	51	44	39	58	50	43	39	36		
		1.0	72	61	53	47	70	60	53	47	67	58	52	46	64	56	50	46	43		
		1.25	78	68	61	55	76	67	60	55	73	65	59	54	69	63	57	53	50		
下方投影面積 等価発光面積	c m ² c m ²	1.5	82	73	66	61	80	72	65	60	77	70	64	59	73	67	62	58	55		
		2.0	88	80	74	69	86	79	73	68	82	76	71	67	79	74	70	66	63		
取付 高さ	器具間隔最大限		2.5	92	85	79	75	90	84	78	74	86	81	76	73	82	78	74	71	68	
	横方向 (A) H m	縦方向 (B) H m	3.0	94	88	83	79	92	87	82	78	88	84	80	77	85	81	78	75	72	
H m	1.30 H m	1.30 H m	4.0	97	93	89	85	95	91	87	84	92	88	85	82	88	86	83	80	77	
			5.0	99	95	92	89	97	94	91	88	94	91	88	86	91	88	86	84	80	
			7.0	101	99	96	93	100	97	95	92	96	94	92	90	93	91	90	88	84	
			10.0	103	101	99	97	101	100	98	96	98	97	95	94	95	94	92	91	87	

