

# 屋内照明器具特性

品番 (品名)	LGB50294										
光源	LED2700_70_4700 x1 4700.0 lm										
管理番号	K0157903(0)D 1										
BZ分類	BZ5										

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	3 %																			
下方光束	97 %																			
室指数	照明率 ( X0.01 ) ZCM																			
保守率	良 0.69 中 0.67 否 0.63	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8	
		0.8	6.6	5.4	4.7	4.1	6.4	5.4	4.6	4.1	6.1	5.2	4.5	4.0	5.8	5.0	4.4	4.0	3.7	
		1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.7	5.9	5.2	4.7	6.4	5.7	5.1	4.7	4.4	
		1.25	7.9	6.9	6.1	5.6	7.7	6.8	6.1	5.5	7.3	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.1	
下方投影面積	c m <sup>2</sup>	1.5	8.3	7.4	6.7	6.1	8.1	7.2	6.6	6.1	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.6	
		2.0	8.8	8.1	7.5	6.9	8.6	7.9	7.4	6.9	8.3	7.7	7.2	6.8	7.9	7.4	7.0	6.7	6.4	
		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.4	8.6	8.1	7.7	7.3	8.3	7.9	7.5	7.2	6.9	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
1.5m	1.97 m	2.23 m	4.0	9.7	9.3	8.9	8.5	9.6	9.1	8.8	8.4	9.2	8.9	8.5	8.3	8.9	8.6	8.3	8.1	7.8
2	2.59	2.75	5.0	9.9	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.4	9.1	8.9	8.6	9.1	8.9	8.6	8.4	8.1
2.5	3.21	3.3	7.0	10.2	9.9	9.6	9.4	10.0	9.7	9.5	9.3	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.8	8.5
3	3.84	3.87	10.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.7	9.5	9.4	9.5	9.4	9.3	9.2	8.8

