

# 屋内照明器具特性

品番 (品名)	L G W 4 5 8 3 4 S	
光源	LDA3L-E17/C/W x1	280.0 l m
管理番号	K0164342(0)DR1	
BZ分類	BZ10	

器具効率	82%	天井	80%				70%				50%				30%				0%	
	上方光束		52%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	30%	床	10%				10%				10%				10%				0%	
室指数			照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	3.4	2.4	1.8	1.3	3.1	2.2	1.6	1.2	2.4	1.7	1.2	0.9	1.7	1.2	0.9	0.6	0.1
	中	0.6	0.6	4.1	3.1	2.4	1.9	3.7	2.8	2.2	1.7	2.8	2.2	1.7	1.3	2.1	1.6	1.2	0.9	0.3
	否	0.56	1.0	4.6	3.6	2.9	2.4	4.1	3.3	2.6	2.2	3.2	2.5	2.1	1.7	2.3	1.9	1.5	1.2	0.5
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	5.0	4.1	3.4	2.9	4.5	3.7	3.1	2.6	3.5	2.9	2.4	2.1	2.6	2.1	1.8	1.5	0.6
			1.5	5.4	4.5	3.8	3.3	4.8	4.1	3.5	3.0	3.7	3.2	2.7	2.4	2.8	2.4	2.0	1.7	1.5
取付高さ	器具間隔最大限		2.5	6.1	5.4	4.9	4.4	5.5	4.9	4.4	4.0	4.3	3.9	3.5	3.2	3.3	2.9	2.7	2.4	1.2
	横方向 (A)	縦方向 (B)	3.0	6.3	5.7	5.2	4.8	5.7	5.2	4.7	4.3	4.5	4.1	3.8	3.5	3.4	3.1	2.9	2.6	1.3
H <sub>m</sub>	H <sub>m</sub>	H <sub>m</sub>	4.0	6.6	6.1	5.7	5.3	6.0	5.5	5.1	4.8	4.8	4.4	4.1	3.9	3.6	3.4	3.2	3.0	1.6
			5.0	6.8	6.4	6.0	5.6	6.1	5.8	5.4	5.1	4.9	4.6	4.4	4.1	3.8	3.6	3.4	3.2	3.0
			7.0	7.0	6.7	6.4	6.1	6.4	6.1	5.8	5.5	5.1	4.9	4.7	4.5	4.0	3.8	3.6	3.5	2.0
			10.0	7.2	6.9	6.7	6.5	6.5	6.3	6.1	5.9	5.3	5.1	5.0	4.8	4.1	4.0	3.9	3.7	2.2

