

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | LGB50206           |  |  |  |  |           |  |  |  |  |
| 光源      | LED5000_70_1038 x1 |  |  |  |  | 1038.0 1m |  |  |  |  |
| 管理番号    | K0157927(0)D 1     |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ5                |  |  |  |  |           |  |  |  |  |

|        |               |                 |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
|--------|---------------|-----------------|------|------|------|-----|------|------|------|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率   | 100 %         | 天井              | 80 % |      |      |     | 70 % |      |      |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|        |               | 壁               | 70   | 50   | 30   | 10  | 70   | 50   | 30   | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
|        |               | 床               | 10 % |      |      |     | 10 % |      |      |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 上方光束   | 3 %           |                 |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
| 下方光束   | 97 %          |                 |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
| 室指数    | 照明率 ( X0.01 ) |                 |      |      |      |     |      |      |      |     |      |     |     |     |      |     | ZCM |     |     |     |
| 保守率    | 良<br>中<br>否   | 0.69            | 0.6  | 5.6  | 4.4  | 3.6 | 3.1  | 5.5  | 4.3  | 3.6 | 3.0  | 5.2 | 4.2 | 3.5 | 3.0  | 5.0 | 4.1 | 3.4 | 3.0 | 2.8 |
|        |               | 0.67            | 0.8  | 6.6  | 5.4  | 4.6 | 4.1  | 6.4  | 5.4  | 4.6 | 4.1  | 6.1 | 5.2 | 4.5 | 4.0  | 5.8 | 5.0 | 4.4 | 4.0 | 3.7 |
|        |               | 0.63            | 1.0  | 7.3  | 6.2  | 5.4 | 4.8  | 7.1  | 6.1  | 5.3 | 4.8  | 6.7 | 5.9 | 5.2 | 4.7  | 6.4 | 5.7 | 5.1 | 4.7 | 4.4 |
|        |               |                 | 1.25 | 7.9  | 6.9  | 6.1 | 5.6  | 7.7  | 6.8  | 6.1 | 5.5  | 7.3 | 6.5 | 5.9 | 5.4  | 7.0 | 6.3 | 5.8 | 5.4 | 5.1 |
| 下方投影面積 |               | cm <sup>2</sup> |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
| 等価発光面積 |               | cm <sup>2</sup> |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
| 取付高さ   | 器具間隔最大限       |                 |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
|        | 横方向 (A)       | 縦方向 (B)         |      |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
| 1.5m   | 1.93m         | 1.98m           | 4.0  | 9.7  | 9.3  | 8.9 | 8.5  | 9.6  | 9.1  | 8.8 | 8.4  | 9.2 | 8.9 | 8.5 | 8.3  | 8.9 | 8.6 | 8.3 | 8.1 | 7.7 |
| 2      | 2.55          | 2.55            | 5.0  | 9.9  | 9.6  | 9.2 | 8.9  | 9.8  | 9.4  | 9.1 | 8.8  | 9.4 | 9.1 | 8.9 | 8.6  | 9.1 | 8.9 | 8.6 | 8.4 | 8.1 |
| 2.5    | 3.18          | 3.14            | 7.0  | 10.2 | 9.9  | 9.6 | 9.4  | 10.0 | 9.7  | 9.5 | 9.3  | 9.7 | 9.4 | 9.2 | 9.0  | 9.4 | 9.2 | 9.0 | 8.8 | 8.5 |
| 3      | 3.82          | 3.75            | 10.0 | 10.3 | 10.1 | 9.9 | 9.7  | 10.2 | 10.0 | 9.8 | 9.6  | 9.8 | 9.7 | 9.5 | 9.4  | 9.5 | 9.4 | 9.3 | 9.2 | 8.8 |

